

**SOLUTION**

L&L Seal

VERSION

March 2021

Induction activated expandable sealant

Solution for rapid reaction sealing.

L-4705 is a sealant material specifically developed to be used with induction activation. An important distinction of the induction activation process is that the heat is generated inside the sealant itself, instead of external heat source via heat conduction.

KEY PRODUCT ATTRIBUTES

- Induction activated sealant
- Induction process < 30 seconds
- Max seal temperature < 425°F
- No high temperature convection ovens needed for curing and sealing
- Dry to the touch

TYPICAL APPLICATION AREAS

- Automotive & Commercial Vehicle Sound Bars
- Commercial Vehicles
- HVAC Units
- Automotive Consoles

llproducts.com

The information contained herein is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty, or guarantee is made regarding its accuracy, reliability, or completeness by L&L Products, Inc. or any of its affiliates. It is the responsibility of the user to assure the suitability and completeness of such information and any depicted product for the particular use of the user. L&L Products, Inc. and its affiliates accept no liability for any loss or damage that may occur from the use of this information or any depicted product. L&L Products, Inc. and its affiliates specifically and expressly disclaim any and all warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, and freedom from claims of infringement of the rights of others associated with the sale or use of any product depicted. L&L Products, Inc. and its affiliates further disclaim any liability for consequential or incidental damages of any kind, including lost profits.

